



Communications Coax Selection Guide Featuring TIMES MICROWAVE SYSTEMS LMR® Flexible Coax



Attenuation (dB per 100 feet ; +25C)

Frequency / Size	2 1/4" LDF	1 5/8" LDF	1 1/4" LDF	LMR-1700	7/8" LDF	LMR-1200	LMR-900	1/2" LDF	LMR-600	LMR-500	1/2" SuperFlex	3/8" LDF	LMR-400	3/8" SuperFlex	Belden 9913	ULTRA-LINK™	RG213/ RG214	1/4" SuperFlex	LMR-300	LMR-240	Belden RG8X	LMR-200	ULTRA-LINK	LMR-195	RG-58	LMR-100A
30 MHz	0.096*	0.120	0.147	0.149	0.197	0.209	0.288	0.369	0.421	0.54	0.561	0.567	0.7	0.654	0.8	0.7	1.2	0.98	1.1	1.3	2.0	1.8	2.5	2.0	2.5	3.9
50 MHz	0.125*	0.156	0.191	0.195	0.257	0.272	0.374	0.479	0.547	0.70	0.730	0.736	0.9	0.848	0.9	--	1.6	1.27	1.4	1.7	2.5	2.3	--	2.6	3.1	5.1
150 MHz	0.227*	0.280	0.340	0.347	0.458	0.481	0.658	0.845	0.964	1.22	1.29	1.30	1.5	1.49	1.6	1.5	2.8	2.23	2.4	3.0	4.7	4.0	5.1	4.4	6.2	8.9
220 MHz	0.281*	0.345*	0.416*	0.427	0.560*	0.589	0.803	1.05*	1.18	1.49	1.58*	1.59*	1.8	1.82*	--	--	3.5	2.72	2.9	3.7	6.0	4.8	--	5.4	7.4	10.9
450 MHz	0.422	0.515	0.617	0.632	0.834	0.864	1.17	1.51	1.72	2.17	2.32	2.30	2.7	2.66	2.8	2.7	5.2	3.93	4.2	5.3	8.6	7.0	9.5	7.8	10.6	15.8
700 MHz	--	--	--	0.809	--	1.10	1.48	--	2.18	2.77	--	--	3.42	--	--	--	--	--	5.1	6.6	--	8.7	--	9.8	--	20.0
900 MHz	0.641*	0.767*	0.912*	0.936	1.23*	1.27	1.70	2.21*	2.50	3.13	3.41*	3.36*	3.9	3.86*	4.2	4.19	8.0	5.67*	6.1	7.6	12.8	9.9	14.0	11.1	16.5	22.8
1,500 MHz	0.879*	1.050	1.22	1.26	1.66	1.69	2.24	2.93	3.31	4.13	4.57	4.43	5.1	5.12	5.6	--	--	7.47	7.9	9.9	--	12.9	--	14.5	--	30.0
2,000 MHz	1.058*	1.250	1.45	1.50	1.97	1.99	2.63	3.45	3.90	4.84	5.41	5.21	6.0	6.01	6.7	--	--	8.73	9.2	11.5	--	15.0	--	16.9	--	35.0
2,500 MHz	--	1.440	1.68*	1.71	2.27*	2.26	2.98	3.91*	4.42	5.48	6.17*	5.91*	6.8	6.84*	--	6.8*	--	9.85*	10.4	12.9	--	16.9	37.0*	19.0	--	40.0
5,800 MHz	--	--	--	--	--	--	4.90	--	7.30	8.90	--	--	10.8	--	--	--	--	--	16.6	20.4	--	26.4	--	28.3	--	64.1


Attenuation at Any Frequency = [k1 x SqRt (Fmhz)] + [k2 x Fmhz] or use Performance Calculator at www.timesmicrowave.com

k1	0.02646	0.03737	0.05177	0.07555	0.09659	0.12229	0.19193	0.24208	0.32090	0.35686	0.70914															
k2	0.00016	0.00016	0.00016	0.00026	0.00026	0.00026	0.00033	0.00033	0.00033	0.00047	0.00174															
List Price \$/foot	20.24	15.76	10.94	\$ 7.80	6.18	\$ 4.85	\$ 3.70	2.50	\$ 1.30	\$ 1.05	3.62	1.89	\$.64	2.64	.97	1.20	1.11/1.75	1.66	\$.53	\$.47	0.68	\$.37	1.40	\$.37	0.42	\$.30



Power Handling (kW ; +40C ; Sea Level)

Frequency / Size	2 1/4" LDF	1 5/8" LDF	1 1/4" LDF	LMR-1700	7/8" LDF	LMR-1200	LMR-900	1/2" LDF	LMR-600	LMR-500	1/2" SuperFlex	3/8" LDF	LMR-400	3/8" SuperFlex	Belden 9913	ULTRA-LINK	RG213/ RG214	1/4" SuperFlex	LMR-300	LMR-240	Belden RG8X	LMR-200	ULTRA-LINK	LMR-195	RG-58	LMR-100A
30 MHz	39.5*	28.9	21.1	20.3	14.0	12.6	8.9	6.31	5.5	4.4	5.75	4.14	3.3	3.97	2.2	--	1.8	2.28	2.1	1.49	0.35	1.02	4.0	0.89	0.40	0.23
50 MHz	30.2*	22.1	16.2	15.6	10.7	9.7	6.8	4.85	4.3	3.4	4.42	3.19	2.6	3.06	1.7	--	1.2	1.76	1.6	1.15	0.28	0.79	--	0.68	0.30	0.18
150 MHz	16.7*	12.3	9.09	8.7	6.04	5.5	3.9	2.75	2.4	1.9	2.49	1.81	1.5	1.74	0.90	--	0.62	1.00	0.93	0.66	0.15	0.45	2.0	0.39	0.16	0.10
220 MHz	13.5*	13.5*	7.45*	7.1	4.94*	4.5	3.2	2.23*	1.9	1.6	2.04*	1.49*	1.2	1.44*	--	--	--	0.825*	0.76	0.54	--	0.37	--	0.32	--	0.08
450 MHz	8.91	6.71	5.01	4.8	3.32	3.1	2.2	1.53	1.3	1.1	1.38	1.02	0.83	0.975	0.45	--	0.30	0.567	0.52	0.38	0.08	0.26	1.0	0.22	0.08	0.06
700 MHz	--	--	--	3.8	--	2.4	1.7	--	1.1	0.85	--	--	0.66	--	--	--	--	--	0.43	0.30	--	0.21	--	0.18	--	0.05
900 MHz	5.90*	4.49*	3.39*	3.3	2.24	2.1	1.5	1.05*	0.93	0.75	0.944*	0.703*	0.58	0.674*	0.28	--	0.18	0.393*	0.36	0.26	0.05	0.18	0.65	0.15	0.05	0.040
1,500 MHz	4.29*	3.30	2.52	2.4	1.66	1.6	1.1	0.793	0.70	0.57	0.705	0.530	0.44	0.507	0.20	--	--	0.299	0.28	0.20	--	0.14	--	0.12	--	0.030
2,000 MHz	3.57*	2.76	2.13	2.0	1.40	1.3	1.0	0.673	0.59	0.49	0.597	0.451	0.37	0.431	0.16	--	--	0.256	0.24	0.17	--	0.12	--	0.10	--	0.025
2,500 MHz	--	2.40	1.84*	1.8	1.21*	1.2	0.9	0.594*	0.52	0.43	0.547*	0.398*	0.33	0.379*	--	--	--	0.225*	0.21	0.15	--	0.10	--	0.09	--	0.020
5,800 MHz	--	--	--	--	--	--	0.52	--	0.32	0.26	--	--	0.21	--	--	--	--	--	0.13	0.10	--	0.07	--	0.06	--	0.010




General Performance Properties

	LMR-1700	LMR-1200	LMR-900	LMR-600	LMR-500	LMR-400	LMR-300	LMR-240	LMR-200	LMR-195	LMR-100A
Conductor: (note 1)	0.527"	0.349"	0.262"	0.176"	0.142"	0.109"	0.070"	0.056"	0.044"	0.037"	0.018"
Dielectric: Cellular PE (note 2)	1.350"	0.920"	0.680"	0.455"	0.370"	0.285"	0.190"	0.150"	0.116"	0.110"	0.060"
Shield: Aluminum Tape (note 3)	1.356"	0.926"	0.686"	0.461"	0.376"	0.291"	0.196"	0.155"	0.121"	0.116"	0.065"
Tinned Copper Braid	1.402"	0.972"	0.732"	0.490"	0.405"	0.320"	0.225"	0.178"	0.144"	0.139"	0.083"
Jacket: Black PE (note 4)	1.670"	1.200"	0.870"	0.590"	0.500"	0.405"	0.300"	0.240"	0.195"	0.195"	0.110"
Bend Radius (note 5)	13.5"	6.5"	3"	1.5"	1.25"	1"	.875"	0.75"	0.50"	0.50"	0.25"
Weight(lbs/foot)	0.736	0.448	0.266	0.131	0.097	0.068	0.055	0.034	0.022	0.022	0.015
Temperature Range	-40°C to +85°C										
Impedance	50 Ohms										
Velocity (%)	89	88	87	87	86	85	85	84	83	80	66
Capacitance (pF per Foot)	22.8	23.1	23.4	23.4	23.6	23.9	24.1	24.2	24.5	24.3	30.8
DC Resistance: center conductor (ohms/1000') : shield	0.21	0.32	0.54	0.53	0.82	1.39	2.12	3.20	5.36	7.58	81.0
Shielding	> 90 db										
Phase Stability	+/- 10 ppm/degC										

NOTES:

- (1) Center Conductor in LMR-900, LMR-1200 & LMR-1700 is Copper Tube
Center Conductor in LMR-400, LMR-500 & LMR-600 is Copper Clad Aluminum
Center Conductor in LMR-195, LMR-200, LMR-240 and LMR-300 is Bare Copper
LMR-100A is BCCS
- (2) Low loss closed cell polyethylene foam (LMR-100A solid polyethylene)
- (3) Aluminum laminated tape bonded (LMR-100A unbonded) to the Dielectric with a Tinned Copper Overbraid
- (4) Black UV protected polyethylene (LMR-100A black PVC)
- (5) Less than 1 ohm impedance change at bend

Trademarks are the exclusive property of their respective owners.
Competitor's Data As Published
*-estimated from published data.



TIMES MICROWAVE SYSTEMS

358 Hall Avenue / P. O. Box 5039
Wallingford, CT 06492-5039 USA
TEL (203) 949-8400 • FAX (203) 949-8423
www.timesmicrowave.com